

ROLLFAB METAL PRODUCTS  
MS-150 LOW-FLOATING ROOF  
& PANEL CLIPS

NAILBASE ROOF SUBSTRATE  
(BY OTHERS)

RMP SA-HT SELF-ADHERING  
UNDERLAYMENT

INSULATION (OPT.)  
(BY OTHERS)

METAL DECKING (OPT.)  
(BY OTHERS)

APPROPRIATE FASTENERS  
@ 12" O.C. MAX

8" (MAX.)

ROLLFAB METAL PRODUCTS MS-150  
MECHANICAL SEAM ROOFING PANEL

DBL BEAD OF BUTYL SEALANT  
FIELD APPLIED TO VERTICALS

MIN. 6" WIDE RMP SA-HT  
SELF-ADHERING UNDERLAYMENT

1" MIN. FIELD NOTCH & HEMMED  
PANEL @ EAVE, ALLOW CLEARANCE  
FOR THERMAL EXPANSION

20GA MIN. OFFSET JOGGLE CLEAT  
SET IN BUTYL TAPE

APPROPRIATE FASTENER  
8" O.C. MAX.

EAVE STARTER FLASHING

APPROPRIATE FASTENER  
8" O.C. MAX.

20GA MIN. EAVE CLEAT W/ RISER

LOW EAVE FASCIA  
(BY OTHERS)



**FLUSH LOW EAVE**

2529 WEST JACKSON ST, PHX, AZ 85009  
PH: (602) 275-1676 FAX: (602) 275-1739

PANEL SYSTEM: MS-150	
ISSUE / REVISION DATE: 1/11/2013	DETAIL NO. <b>MS150-FLE</b>
NOT TO SCALE	