

ROLLFAB METAL PRODUCTS
MS200 LOW-FLOATING ROOF
PANEL CLIPS

NAILBASE ROOF SUBSTRATE
(BY OTHERS)

RMP SA-HT SELF-ADHERING
UNDERLAYMENT

INSULATION (OPT.)
(BY OTHERS)

METAL DECKING (OPT.)
(BY OTHERS)

APPROPRIATE FASTENERS
@ 12" O.C. MAX

8" (MAX.)

DBL BEAD OF BUTYL SEALANT
FIELD APPLIED TO VERTICALS

MIN. 6" WIDE RMP SA-HT
SELF-ADHERING UNDERLAYMENT

1" MIN. FIELD NOTCH & HEMMED
PANEL @ EAVE, ALLOW CLEARANCE
FOR THERMAL EXPANSION

20GA MIN. OFFSET JOGGLE CLEAT
SET IN BUTYL TAPE

APPROPRIATE FASTENER
8" O.C. MAX.

EAVE STARTER FLASHING

APPROPRIATE FASTENER
8" O.C. MAX.

20GA MIN. EAVE CLEAT W/ RISER

LOW EAVE FASCIA
(BY OTHERS)

RMP
ROLLFAB
METAL PRODUCTS
www.rollfabmetal.com

FLUSH LOW EAVE

2529 WEST JACKSON ST, PHX, AZ 85009
PH: (602) 275-1676 FAX: (602) 275-1739

PANEL SYSTEM: MS-200

ISSUE / REVISION
DATE:
1/11/2013

DETAIL NO.
MS2-FLE

NOT TO SCALE