



ROLLFAB METAL PRODUCTS  
SL-175 ROOF PANEL CLIPS

NAILBASE ROOF SUBSTRATE  
(BY OTHERS)

RMP SA-HT SELF-ADHERING  
UNDERLAYMENT

INSULATION (OPT.)  
(BY OTHERS)

METAL DECKING (OPT.)  
(BY OTHERS)

APPROPRIATE FASTENERS  
@ 12" O.C. MAX

8" (MAX.)

ROLLFAB METAL PRODUCTS  
SL-175 STANDING SEAM ROOFING PANEL

DBL BEAD OF BUTYL SEALANT  
FIELD APPLIED TO VERTICALS

MIN. 6" WIDE RMP SA-HT  
SELF-ADHERING UNDERLAYMENT

20GA MIN. OFFSET JOGGLE CLEAT  
SET IN BUTYL TAPE

1" MIN. FIELD NOTCH & HEMMED  
PANEL @ EAVE, ALLOW CLEARANCE  
FOR THERMAL EXPANSION

#44 X 1/4" BLIND PAINTED  
RIVETS @ EACH STRAP

GUTTER STRAPPING @  
24" SPACING O.C.

GUTTER @ LOWER EAVE

DOWNSPOUT

**\*NOTE: SLIDING SNOW AND ICE COULD  
CAUSE DAMAGE TO GUTTER SYSTEM.**



**GUTTER @ LOWER EAVE**

2529 WEST JACKSON ST, PHX, AZ 85009  
PH: (602) 275-1676 FAX: (602) 275-1739

PANEL SYSTEM: SL-175	
ISSUE / REVISION DATE: 1/11/2013	DETAIL NO. SL175-GTR
NOT TO SCALE	