



ROLLFAB METAL PRODUCTS
SL-175 STANDING SEAM
ROOFING PANEL

ROLLFAB METAL PRODUCTS
SL-175 ROOF PANEL CLIPS

NAILBASE ROOF SUBSTRATE
(BY OTHERS)

RMP SA-HT SELF-ADHERING
UNDERLAYMENT

INSULATION (OPT.)
(BY OTHERS)

METAL DECKING (OPT.)
(BY OTHERS)

#44 x 1/8" BLIND PAINTED
RIVETS APPLIED @ 6" O.C.

METAL Z-CLOSURE SET IN
NON-SKINNING BUTYL SEALANT
(SEE FASTENER SEQUENCE)

FIELD NOTCH AND BEND PANEL
FACE 1 1/2" MIN., CAULK VERTICALS
W/ NON-SKINNING BUTYL SEALANT

MIN. 6" WIDE RMP SA-HT
SELF-ADHERED UNDERLAYMENT

APPROPRIATE FASTENERS
STAGGERED @ 24" O.C.

HIGH EAVE (PEAK CAP)
FLASHING

22GA. MIN HIGH EAVE CLEAT
W/ APPROPRIATE FASTENER
@ 24" O.C.

FIELD CRIMP @ 12" O.C.

HIGH EAVE FASCIA
(BY OTHERS)

8" MAX.



HIGH EAVE

2529 WEST JACKSON ST, PHX, AZ 85009
PH: (602) 275-1676 FAX: (602) 275-1739

PANEL SYSTEM: SL-175

ISSUE / REVISION
DATE:
1/28/13

DETAIL NO.
SL175-HE

NOT TO SCALE