

ROLLFAB METAL PRODUCTS
SL-175 STANDING SEAM ROOFING
& PANEL CLIPS @ 18" O.C. MAX

NAILBASE ROOF SUBSTRATE
(BY OTHERS)

RMP SA-HT SELF-ADHERING
UNDERLAYMENT

INSULATION (OPT.)
(BY OTHERS)

METAL DECKING (OPT.)
(BY OTHERS)

APPROPRIATE FASTENER
@ 24" O.C.

#44 x 1/8" BLIND PAINTED
RIVETS APPLIED @ 36" O.C.

METAL Z-CLOSURE SET IN
NON-SKINNING BUTYL SEALANT
1/4" - 14 x 7/8" STITCH W/ NEO WASHER

CUT PANEL AND BEND UP 1 1/2" @ 90°

MIN. 6" WIDE RMP SA-HT
SELF-ADHERING UNDERLAYMENT

RAKE GABLE FLASHING

22GA MIN. RAKE GABLE CLEAT
APPROPRIATE FASTENER
@ 24" O.C.

FIELD CRIMP @ 12" O.C.

RAKE / GABLE FASCIA
(BY OTHERS)

RMP
ROLLFAB
METAL PRODUCTS
www.rollfabmetal.com

OFF MODULE RAKE / GABLE W/ ZEE

2529 WEST JACKSON ST, PHX, AZ 85009
PH: (602) 275-1676 FAX: (602) 275-1739

PANEL SYSTEM: SL-175

ISSUE / REVISION
DATE:
1/28/13

DETAIL NO.
SL175-RGZ

NOT TO SCALE