

ROLLFAB METAL PRODUCTS
SL-175 STANDING SEAM
ROOFING PANEL

ROLLFAB METAL PRODUCTS
SL-175 ROOF PANEL CLIPS

DBL BEAD OF BUTYL SEALANT
FIELD APPLIED TO VERTICALS

20GA MIN. OFFSET JOGGLE CLEAT
SET IN BUTYL TAPE

MIN. 6" WIDE RMP SA-HT
SELF-ADHERING UNDERLAYMENT

9" (MAX.)

6"-9"

NAILBASE ROOF SUBSTRATE
(BY OTHERS)

INSULATION (OPT.)
(BY OTHERS)

METAL DECKING (OPT.)
(BY OTHERS)

APPROPRIATE FASTENER
24" O.C.

APPROPRIATE FASTENER
8" O.C. MAX.

VALLEY FLASHING

1" MIN. FIELD NOTCH & HEMMED
PANEL @ CLEAT, ALLOW
CLEARANCE FOR THERMAL
EXPANSION



VALLEY FLASHING

2529 WEST JACKSON ST, PHX, AZ 85009
PH: (602) 275-1676 FAX: (602) 275-1739

PANEL SYSTEM: SL-175

ISSUE / REVISION
DATE:
1/28/2013

DETAIL NO.
SL175VLY

NOT TO SCALE