

ROLLFAB METAL PRODUCT  
SL-175 STANDING ROOF &  
ROOF PANEL CLIPS

NAILBASE ROOF SUBSTRATE  
(BY OTHERS)

RMP SA-HT SELF-ADHERING  
UNDERLAYMENT

INSULATION (OPT.)  
(BY OTHERS)

METAL DECKING (OPT.)  
(BY OTHERS)

APPROPRIATE FASTENERS  
@ 12" O.C. MAX

8" (MAX.)

ROLLFAB METAL PRODUCTS  
MS-200 MECHANICAL SEAM  
ROOFING PANEL

DBL BEAD OF BUTYL SEALANT  
FIELD APPLIED TO VERTICALS

MIN. 6" WIDE RMP SA-HT  
SELF-ADHERING UNDERLAYMENT

1" MIN. FIELD NOTCH & HEMMED  
PANEL @ EAVE

CLEARANCE FOR THERMAL  
EXPANSION & CONTRACTION

APPROPRIATE FASTENER 8" O.C. MAX.

EAVE STARTER FLASHING

APPROPRIATE FASTENER  
12" O.C. MAX.

22GA MIN. EAVE CLEAT (OPTIONAL)

LOW EAVE FASCIA  
(BY OTHERS)



**EXTENDED LOW EAVE**

2529 WEST JACKSON ST, PHX, AZ 85009  
PH: (602) 275-1676 FAX: (602) 275-1739

PANEL SYSTEM: SL-175	
ISSUE / REVISION DATE: 1/11/2013	DETAIL NO. <b>SL175-ELE</b>
NOT TO SCALE	