



FILL W/ COLOR MATCH BUTYL CAULKING

#44 x 1/8" BLIND PAINTED RIVETS APPLIED @ 36" O.C. W/ 1" BEAD BUTYL TAPE SPANNED ACROSS ZEE & RAKE CLEAT

24GA MIN. RAKEWALL CLEAT

ROLLFAB METAL PRODUCTS SL-175 STANDING SEAM ROOFING PANEL

NAILBASE ROOF SUBSTRATE (BY OTHERS)

RMP SA-HT SELF-ADHERING UNDERLAYMENT

INSULATION (OPT.) (BY OTHERS)

METAL DECKING (OPT.) (BY OTHERS)

RAKE WALL FLASHING APPROPRIATE FASTENER @ 24" O.C.

SEAL CLEAT TO UNDERLAYMENT W/ NON-SKINNING BUTYL SEALANT

MIN. 6" WIDE RMP SA-HT SELF-ADHERING UNDERLAYMENT

METAL Z-CLOSURE SET IN NON-SKINNING BUTYL SEALANT ATTACH W/ 1/4" - 14 x 7/8" STITCH SCREWS W/ NEO WASHERS @ 24" OC.

APPROPRIATE FASTENER @ 24" O.C.



OFF MODULE RAKE / WALL W/ZEE

2529 WEST JACKSON ST, PHX, AZ 85009
 PH: (602) 275-1676 FAX: (602) 275-1739

PANEL SYSTEM: SL-175	
ISSUE / REVISION DATE: 1/28/13	DETAIL NO. SL175-RWZ
NOT TO SCALE	